



| Pin | Symbol |
|-----|------------|
| 1 | N.C. (GND) |
| 2 | VLSS |
| 3 | VSS |
| 4 | N.C. |
| 5 | VD0 |
| 6 | BS1 |
| 7 | BS2 |
| 8 | CS# |
| 9 | RES# |
| 10 | D.C# |
| 11 | R/W# |
| 12 | E/RD# |
| 13 | D0 |
| 14 | D1 |
| 15 | D2 |
| 16 | D3 |
| 17 | D4 |
| 18 | D5 |
| 19 | D6 |
| 20 | D7 |
| 21 | IREF |
| 22 | VCOMH |
| 23 | VCC |
| 24 | N.C. (GND) |

Notes:

1. Color: Light Blue
2. Driver IC: SSD1309
3. Interface:
8-bit 68XX/80XX Parallel, 4-wire SPI, I2C
4. General Tolerance: ±0.30
5. The total thickness (1.90 Max) is without protective film.
The actual assembled total thickness with above materials should be 2.00 Max.

| | | | |
|--------------------------------|-------|-------------|--|
| CUSTOMER APVL | | DATE | |
| DRAWN | SCALE | TITLE | |
| DFTG CHK | UNIT | MI12832AO-B | |
| ENGR CHK | mm | MODEL | |
| APPROVAL | | DWG NO | |
| MULTI-INNO TECHNOLOGY CO.,LTD. | | PAGE | |
| | | 1/1 | |