


Pin	Symbol
1	NC
2	VSDH
3	VDDH
4	VSSH
5	IREF
6	OSCA2
7	OSCA1
8	VDDIO
9	VSYNCO
10	VSYNCL
11	HSYNCL
12	DOTCLK
13	ENABLE
14	CPU
15	PS
16	D17
17	D16
18	D15
19	D14
20	D13
21	D12
22	D11
23	D10
24	D9
25	RS
26	CSB
27	RDB
28	WRB
29	RESETB
30	VSS
31	VDD
32	VSSH
33	VDDH
34	VSDH
35	NC



- Notes:
1. Driver IC: SEPS525
 2. Die Size: 19660um x 1850um
 3. COF Number: SEPS525-F00
 4. Interface: 6-/8-/9-/bit 68XX/80XX Parallel, 6bit-RGB I/F, 4-wire SPI
 5. General Tolerance: ±0.30
 6. The total thickness (1.70 Max) is without Polarizer protective film & Remove Tape.
The actual assembled total thickness with above materials should be 1.85 Max

CUSTOMER APVL		CUSTOMER		DATE	
DRAWN		SCALE		TITLE	
DFTG CHK		UNIT	mm	MI160128AO	
ENGR CHK				MODEL	
APPROVAL				DWC NO	
MULTI-INNO TECHNOLOGY CO.,LTD.				PAGE	1/1