



(Reference Mechanical Design)



Detail "A"  
Scale (10:1)

Pin	Symbol
1	N.C. (GND)
2	VSDH
3	VDDH
4	VSSH
5	IBEF
6	OSCA2
7	OSCA1
8	VDDIO
9	VSYNCO
10	VSYNCS
11	HSYNC
12	DOTCLK
13	ENABLE
14	CPU
15	PS
16	D17
17	D16
18	D15
19	D14
20	D13
21	D12
22	D11
23	D10
24	D9
25	RS
26	CSB
27	RDB
28	WRB
29	RESETB
30	VSS
31	VDD
32	VSSH
33	VDDH
34	VSDH
35	N.C. (GND)

Notes:

1. Driver IC: SEPS525
2. Die Size: 19660um x 1850um
3. COF Number: SEPS525F00
4. Interface:  
8-/9-bit 80XX Parallel, 4-wire SPI, 6-bit RGB I/F
5. General Tolerance: ±0.30
6. The total thickness (1.70 Max) is without polarizer protective film & remove tape.  
The actual assembled total thickness with above materials should be 1.95 Max

CUSTOMER APVL	CUSTOMER	DATE	TITLE	
DRAWN	SCALE	UNIT	MI160128BO	
DFTG CHK	UNIT	mm	MODEL	
ENGR CHK	APPROVAL		MODEL	
MULTI-INNO TECHNOLOGY CO.,LTD.			DWG NO	PAGE
				1/1