



| Pin Assignment | |
|----------------|----------|
| NO. | SYMBOL |
| 1 | NC (GND) |
| 2 | C2P |
| 3 | C2N |
| 4 | C1P |
| 5 | C1N |
| 6 | VBAT |
| 7 | VSS |
| 8 | VDD |
| 9 | BS1 |
| 10 | BS2 |
| 11 | CS# |
| 12 | RES# |
| 13 | D/C# |
| 14 | R/W# |
| 15 | E/RD# |
| 16 | D0 |
| 17 | D1 |
| 18 | D2 |
| 19 | D3 |
| 20 | D4 |
| 21 | D5 |
| 22 | D6 |
| 23 | D7 |
| 24 | IREF |
| 25 | VCOMH |
| 26 | VCC |
| 27 | VLSS |
| 28 | NC (GND) |

Specification

1. Display: OLED (White)
2. Format: 64*48
3. Driver IC: SSD1306Z
4. General Tolerance: ±0.3
5. Operate temp: -40°C ~ 70°C
Storage temp: -40°C ~ 85°C
6. DUTY: 1/48
7. RoHS Compliant

| | | | |
|--------------------------------|-------|------------|--|
| CUSTOMER APVL | | DATE | |
| DRAWN | SCALE | TITLE | |
| DFTG CHK | UNIT | MI6448CO-W | |
| ENGR CHK | mm | MODEL | |
| APPROVAL | | DWG NO | |
| MULTI-INNO TECHNOLOGY CO.,LTD. | | PAGE | |
| | | 1/1 | |