


The hole for nominal size 3mm se lf-tapping screw attachment depth 3.5mm(4 p oint)
Suggested applying torque 0.15-0.2Nm

CN1 Pin Assign

Pin No.	Symbol
1	GND
2	CK
3	Hsync
4	Vsync
5	GND
6	R0
7	R1
8	R2
9	R3
10	R4
11	R5
12	GND
13	G0
14	G1
15	G2
16	G3
17	G4
18	G5
19	GND
20	B0
21	B1
22	B2
23	B3
24	B4
25	B5
26	GND
27	ENAB
28	VCC
29	VCC
30	R/L
31	U/D
32	NC
33	GND

CN2 Pin Assign

PIN#	Symbol	Cable color
1	AN1	Red
2	AN2	Red
3	AN3	Red
4	CA1	White
5	CA2	Blue
6	CA3	Black



Notes:

1. unmarked tolerance: ±0.50mm;
2. Display Type: a-Si TFT ;
3. Operating Temperature: -20°C~+70°C;
4. Storage Temperature: -30°C~+85°C;
5. Gray Scale Inversion: 12 o'clock;
Viewing Direction: 6 o'clock;
6. CN2 LED Power source Connector: SHLP-06V-S-B(JST) or Compatible,
Mating Connector: SM06B-SHLS-TF(JST) or Compatible;
7. CN1 Connector type: 089H33-000100-G2-R (STARCONN)
8. Requirement on Environment Protection: RoHS Compliant.

CUSTOMER APVL	CUSTOMER	DATE	TITLE
DRAWN	SCALE	MI0570B1T	
DFTG CHK	UNIT	mm	
ENGR CHK	APPROVAL	MODEL	
MULTI-INNO TECHNOLOGY CO.,LTD.			DWG NO
			PAGE 1/1