



Detail A
CN5 definition

- Note: 1. Tolerance is ± 0.5 unless otherwise noted.
 2. CN 4 connector: 08-6210-033-340-800(ELCO) or equivalent
 3. Brightness : 400cd/m² (Typ) 320cd/m² (Min)
 4. for RoHS
 5. * is important dimension.
 6. zzzz is mylar tape, T=0.1mm
 7. B/L matching connector is: SM02B-BHSS-1-TB or equivalent.

BHSR-02VS-1(JST) or equivalent

CN 2 define

- | | |
|----------|----------|
| 1. SPENA | 9. D2 |
| 2. SPCK | 10. D1 |
| 3. SPDA | 11. D0 |
| 4. D7 | 12. DGND |
| 5. D6 | 13. CLK |
| 6. D5 | 14. DGND |
| 7. D4 | 15. DVDD |
| 8. D3 | 16. DVDD |

CN3 & CN4 define

- | | | |
|--------------|---------|---------|
| 1. GND | 12. GND | 23. B3 |
| 2. CLK1 | 13. G0 | 24. B4 |
| 3. HS(HSYNC) | 14. G1 | 25. B5 |
| 4. VS(VSYNC) | 15. G2 | 26. GND |
| 5. GND | 16. G3 | 27. DE |
| 6. R0 | 17. G4 | 28. VCC |
| 7. R1 | 18. G5 | 29. VCC |
| 8. R2 | 19. GND | 30. R/L |
| 9. R3 | 20. B0 | 31. U/D |
| 10. R4 | 21. B1 | 32. NC |
| 11. R5 | 22. B2 | 33. GND |

CUSTOMER APVL	CUSTOMER	DATE	
DRAWN	SCALE	TITLE	
DFTG CHK	UNIT	MI0570IT-3	
ENGR CHK	mm	MODEL	
APPROVAL		DWG NO	
MULTI-INNO TECHNOLOGY CO.,LTD.			PAGE
			1/1