


接口定义

PIN	SYMBOL
1	NC
2	NC
3	CP5
4	CP6
5	CP7
6	CP8
7	NC
8	NC
9	NC
10	VCOML
11	VCOMH
12	AGND
13	NC
14	AVDD
15	CP1
16	CP2
17	PWM
18	FB
19	LED-
20	NC
21	NC
22	LED+
23	GND
24	VDD(3.3V)
25	VSYNC
26	HSYNC
27	DCLK
28	D0
29	D1
30	D2
31	D3
32	D4
33	D5
34	D6
35	D7
36	SDA
37	SCL
38	CS
39	NC
40	GREST



- NOTES:
1. DISPLAY TYPE: 2.36" TFT TRANSMISSIVE
  2. LCD VIEW DIRECTION: 6°CLOCK
  3. LCD DRIVER IC: OTA5182A
  4. BACK LIGHT: 2CHIP WHITE LED; PARALLEL
  5. STORAGE TIME: -30° -80°
  6. OPERATING TIME: -20° -70°
  7. GENERAL TOLERANCE: ±0.2
  8. RoHS compliant.

CUSTOMER APVL	CUSTOMER	DATE	
DRAWN	SCALE	TITLE	
DFTG CHK	UNIT	MI0236AT-1	
ENGR CHK	mm	MODEL	
APPROVAL			
MULTI-INNO TECHNOLOGY CO.,LTD.		DWG NO	PAGE
			1/1