



CTP FPC PIN OUT:		TFT FPC PIN OUT:	
1	TP_VDD	1	LEDK
2	TP_/RES	2	LEDA1
3	TP_/INT	3	LEDA2
4	TP_SDA	4	LEDA3
5	TP_SCK	5	LEDA4
6	TP_GND	6	IM0
		7	IM1
		8	IM2
		9	IM3
		10	RESET
		11	VSYNC
		12	HSYNC
		13	DOTCLK
		14	DE
		15	DB17
		16	DB16
		17	DB15
		18	DB14
		19	DB13
		20	DB12
		21	DB11
		22	DB10
		23	DB9
		24	DB8
		25	DB7
		26	DB6
		27	DB5
		28	DB4
		29	DB3
		30	DB2
		31	DB1
		32	DB0
		33	SD0
		34	SD1
		35	RD
		36	WRX(D/CX)
		37	D/CX(SCL)
		38	CSX
		39	TE
		40	VDDI
		41	VDDI
		42	VCI
		43	GND
		44	NC
		45	NC
		46	NC
		47	NC
		48	GND
		49	GND
		50	GND

NOTES(TFT):

1. DISPLAY TYPE: TFT
2. VIEWING DIRECTION: 6:00
3. POLARIZER MODE: TRANSMISSIVE
4. DRIVE METHOD: 1/320 DUTY
5. VDDI=2.8V,VCI=2.8V
6. OPERATING TEMP: -20°C -- +70°C
7. STORAGE TEMP: -30°C -- +80°C
8. LCD DRIVE IC: ILI9341
9. CONNECTION: FPC
10. BACKLIGHT: 4CHIP-WHITE LED/80mA/3.2V(TYP)
11. UNMARKED TOLERANCE: ±0.20
12. REQUIREMENTS ON ENVIRONMENTAL PROTECTION: RoHS
13. THE CONTROLLED DIMENSION MASK TO BE ()
14. REFERENCE DIMENSION MASK TO BE ()

NOTE(CTP):

1. CAPACITIVE TOUCH PANEL;
2. IC: FT6236, G/G, SINGLE-TOUCH+TWO-TOUCH GESTURE;
3. SURFACE HARDNESS OF C/L: >=6H.
4. INPUT VOLTAGE: 2.8V-3.3V;
5. RESOLUTION: 240*320;

01	FIRST ISSUE	2015.08.26
VER.	REVISED DESCRIPTION	DATE

MULTI-INNO TECHNOLOGY CO.,LTD.

DRAWN BY:	VICTOR 20150826	SCALE : 1/1	MODULE P/N:
CHECKED BY:		UNIT:	MI0283QT-13CP13
APPROVED BY:		mm	DESCRIPTION:
VERSION NO:	01		