



PIN	SYMBOL
1	GND
2	NC
3	NC
4	NC
5	NC
6	GND
7	VCC
8	IOVCC
9	FMARK
10	CS
11	RS
12	WR
13	RD
14	DB00
15	DB01
16	DB02
17	DB03
18	DB04
19	DB05
20	DB06
21	DB07
22	DB08
23	DB09
24	DB10
25	DB11
26	DB12
27	DB13
28	DB14
29	DB15
30	RESET
31	IMO
32	GND
33	A1
34	A2
35	A3
36	A4
37	A5
38	K
39	GND
40	GND

NOTES:

1. DISPLAY TYPE: TFT, TRANSMISSIVE
2. OPERATING VOLTAGE: VCC=2.8V
3. VIEWING DIRECTION: 9 O'CLOCK.
4. IC DRIVER: ILI9341
5. OPERATING TEMP: -20°C ~ 70°C.
6. STORAGE TEMP: -30°C ~ 80°C.
7. LED BACKLIGHT: 5-CHIP WHITE LED.
8. SURFACE LUMINANCE: 360cd/m<sup>2</sup>.
9. GENERAL TOLERANCE: ±0.2.
10. RECOMMENDED CASE OPEN AREA SHOULD BE LESS THAN LCD V.A.
11. RoHS COMPLIANT.

		CUSTOMER APVL	DATE	2014/07/04
		DRAWN	SCALE	TITLE
		DFTG CHK	UNIT	MI0320L1T-5
		ENGR CHK	mm	MODEL
		APPROVAL		
01	FIRST ISSUE	2014.07.04	DWG NO	
VER.	CONTENT	DATE	01	PAGE
MULTI-INNO TECHNOLOGY CO.,LTD.			01	1/1