


PIN DESCRIPTION

PIN	DESCRIPTION
1	LEDK
2	LEDA
3	GND
4	VCC
5	R0
6	R1
7	R2
8	R3
9	R4
10	R5
11	R6
12	R7
13	G0
14	G1
15	G2
16	G3
17	G4
18	G5
19	G6
20	G7
21	B0
22	B1
23	B2
24	B3
25	B4
26	B5
27	B6
28	B7
29	GND
30	CLK
31	DISP
32	HSYNC
33	VSYNC
34	DEN
35	NC
36	GND
37	XR
38	YD
39	XL
40	YU



LED CIRCUIT

Specification:

- 1). Viewing angle: 12 0'clock
- 2). Display mode: a-Si TFT/Transmissive/Normal White
- 3). Operating temp.: -20°C~+70°C
Storage temp.: -30°C~+80°C
- 4). IC: OTA5180A
- 5). All the raw material are Rohs complicant
- 6). Dimensions with mark "*" are important, with mark "()" are referenced

CUSTOMER APVL	CUSTOMER	DATE	TITLE
DRAWN	SCALE	MI0430J3T-4	
DFTG CHK	UNIT	MODEL	
ENGR CHK	mm	DWG NO	
APPROVAL		PAGE 1/1	
MULTI-INNO TECHNOLOGY CO.,LTD.			