


PIN DESCRIPTION

| | |
|----|-------|
| 1 | LEDK |
| 2 | LEDA |
| 3 | GND |
| 4 | VCC |
| 5 | R0 |
| 6 | R1 |
| 7 | R2 |
| 8 | R3 |
| 9 | R4 |
| 10 | R5 |
| 11 | R6 |
| 12 | R7 |
| 13 | G0 |
| 14 | G1 |
| 15 | G2 |
| 16 | G3 |
| 17 | G4 |
| 18 | G5 |
| 19 | G6 |
| 20 | G7 |
| 21 | B0 |
| 22 | B1 |
| 23 | B2 |
| 24 | B3 |
| 25 | B4 |
| 26 | B5 |
| 27 | B6 |
| 28 | B7 |
| 29 | GND |
| 30 | CLK |
| 31 | DISP |
| 32 | HSYNC |
| 33 | VSYNC |
| 34 | DEN |
| 35 | NC |
| 36 | GND |
| 37 | XR |
| 38 | YD |
| 39 | XL |
| 40 | YU |



Specification:

- 1). Viewing angle: 12 0'clock
- 2). Display mode: a-Si TFT/Transmissive/Normal White
- 3). Operating temp.: -20°C~+70°C
Storage temp.: -30°C~+80°C
- 4). IC: OTA5180A
- 5). All the raw material are Rohs complicant
- 6). Dimensions with mark "*" are important, with mark "()" are referenced

| | | | |
|--------------------------------|----------|-----------|------|
| CUSTOMER APVL | CUSTOMER | DATE | |
| DRAWN | SCALE | TITLE | |
| DFTG CHK | UNIT | MI0430J3T | |
| ENGR CHK | mm | MODEL | |
| APPROVAL | | | |
| MULTI-INNO TECHNOLOGY CO.,LTD. | | DWG NO | PAGE |
| | | | 1/1 |