


16-BIT MODE(CN2)	
Pin No.	Symbol
1	GND
2	VCC
3	BL_E
4	RS
5	/WR
6	/RD
7	DB0
8	DB1
9	DB2
10	DB3
11	DB4
12	DB5
13	DB6
14	DB7
15	DB8
16	DB9
17	DB10
18	DB11
19	DB12
20	DB13
21	DB14
22	DB15
23	NC
24	NC
25	/CS
26	/RST
27	NC
28	NC
29	NC
30	NC
31	NC
32	DISP

NOTES:

1. DISPLAY TYPE: TN TFT
2. VIEWING DIRECTION: 6:00
3. POLARIZER MODE: TRANSMISSIVE/POSITIVE
4. VCC=3.3V(TYP)
5. OPERATING TEMP: -20° C -- +70° C
6. STORAGE TEMP: -30° C -- +80° C
7. LCD CONTROLLER: SSD1963
8. INTERFACE: 16-BIT 8080 MPU
9. BACKLIGHT: WHITE LED
10. UNMARKED TOLERANCE: ±0.30mm
11. REQUIREMENTS ON ENVIRONMENTAL PROTECTION: RoHS



CUSTOMER APVL	CUSTOMER	DATE	2012/12/18
DRAWN BY	JACK	SCALE	1/1
DFTG CHK		UNIT	mm
ENGR CHK			
APPROVAL			
MULTI-INNO TECHNOLOGY CO.,LTD.		DWG NO	V01
		PAGE	1