



补PT, 总厚度为 : 0.3mm

PIN	SYMBOL	FUNCTION
1	VLED-	
2	VLED+	
3	GND	
4	VDD	
5	R0	
6	R1	
7	R2	
8	R3	
9	R4	
10	R5	
11	R6	
12	R7	
13	G0	
14	G1	
15	G2	
16	G3	
17	G4	
18	G5	
19	G6	
20	G7	
21	B0	
22	B1	
23	B2	
24	B3	
25	B4	
26	B5	
27	B6	
28	B7	
29	GND	
30	CLKIN	
31	STBYB	
32	HSD	
33	VSD	
34	DEN	
35	NC	
36	GND	
37	XR	
38	YD	
39	XL	
40	YU	

NOTES:

1. DISPLAY TYPE: TFT, TRANSMISSIVE, NORMALLY WHITE
2. OPERATION VOLTAGE: VDD=3.3V
3. VIEWING DIRECTION: 12 O'CLOCK.
4. IC DRIVER: HX8664B+HX8264D
5. OPERATING TEMP: -20°C ~ 70°C.
6. STORAGE TEMP: -30°C ~ 80°C.
7. LED BACKLIGHT: 12-LED WHITE.
8. GENERAL TOLERANCE: ±0.2.
9. RoHS COMPLIANT.

CUSTOMER APVL		DATE	2013/12/05
DRAWN	SCALE	TITLE	
DFTG CHK	UNIT	MI0500PT-6	
ENGR CHK	mm	MODEL	
APPROVAL		MODEL	
MULTI-INNO TECHNOLOGY CO.,LTD.		DWG NO	PAGE
			1/1