



40 PIN FUNCTIONS									
1	U/D	11	Y1	21	G5	31	R3		
2	NC	12	ADJ	22	G4	32	VSS		
3	HSYNC	13	B5	23	G3	33	R2		
4	VLED	14	B4	24	VSS	34	R1		
5	VLED	15	B3	25	G2	35	R0		
6	VLED	16	VSS	26	G1	36	X1		
7	VCC	17	B2	27	G0	37	Y2		
8	VSYNC	18	B1	28	VSS	38	DCLK		
9	DE	19	B0	29	R5	39	VSS		
10	X2	20	VSS	30	R4	40	L/R		

Note:

- Brightness : 500 cd/m² (Typ) 400 cd/m² (Min)
- 40 PIN Connector: JAE FA5B040HP1 or Equivalent.
- 10 PIN Connector: Molex: 54548-1071 or Equivalent.
- Tolerance is ±0.3 unless otherwise noted.
- For RoHS & REACH.
- * is important dimension.

CUSTOMER APVL		CUSTOMER		DATE	
DRAWN	SCALE	TITLE			
DFTG CHK	UNIT	MI0570KT-10			
ENGR CHK	mm	MODEL			
APPROVAL		DWG NO		PAGE	
MULTI-INNO TECHNOLOGY CO.,LTD.				1/1	