



SMD-LED: 3*8=24PCS
20mA*8=160mA

LED circuit

NOTE:

1. Tolerance is ± 0.3 unless otherwise noted.
2. For RoHS.
3. * is important dimension.
4. CN1 connector: Hirose DF14A-20P-1.25H or equivalent, matching side connector: Hirose DF14-20S-1.25C or equivalent.
5. CN6 connector: Hirose DF14A-5P-1.25H or equivalent, matching side connector: Hirose DF14-5S-1.25C or equivalent.

CN6 PIN FUNCTION

1 VDD	3 GND	5 ADJ
2 VDD	4 GND	

CN1 PIN FUNCTION

1 Vcc	6 RxIN0+	11 RxIN2-	16 GND
2 Vcc	7 GND	12 RxIN2+	17 VDD
3 GND	8 RxIN1-	13 GND	18 VDD
4 GND	9 RxIN1+	14 CKIN-	19 GND
5 RxIN0-	10 GND	15 CKIN+	20 ADJ

CUSTOMER APVL	CUSTOMER	DATE	
DRAWN	SCALE	TITLE	
DFTG CHK	UNIT	MI0700J1T-2	
ENGR CHK	mm	MODEL	
APPROVAL			
MULTI-INNO TECHNOLOGY CO.,LTD.		DWG NO	PAGE 1/1