



Note:

1. Tolerance is ±0.3 unless otherwise noted.
2. * is important dimension.
3. Center brightness: 250 cd/m²(Typ.) 200 cd/m²(Min.)
4. Connector A (51 Pin):Vigorconn F82151-H1210PI.
Connector Type:Bottom Contact,Hight:1.1mm Max.
5. For RoHS.

Connector A DEFINE										
1	NC	14	VDD	27	GND	40	AVDD			
2	NC	15	NC	28	RXCLKIN-	41	GND			
3	NC	16	Reset	29	RXCLKIN+	42	LED-			
4	NC	17	STBYB	30	GND	43	LED-			
5	NC	18	GND	31	RXIN3-	44	L/R			
6	NC	19	RXIN0-	32	RXIN3+	45	U/D			
7	NC	20	RXIN0+	33	GND	46	VGL			
8	NC	21	GND	34	NC	47	CABCEN1			
9	GND	22	RXIN1-	35	NC	48	CABCENO			
10	GND	23	RXIN1+	36	GND	49	VGH			
11	GND	24	GND	37	NC	50	LED+			
12	VCOM	25	RXIN2-	38	DIMO	51	LED+			
13	VDD	26	RXIN2+	39	SELB					

CUSTOMER APVL			DATE		2014/07/27	
DRAWN			SCALE : 1/1		TITLE	
DFTG CHK			UNIT		MI0900DT-3	
ENGR CHK			mm		MODEL	
APPROVAL						
01	FIRST ISSUE	2014.07.27	MULTI-INNO TECHNOLOGY CO.,LTD.			DWG NO
VER.	CONTENT	DATE				01
						PAGE
						1/1