



PIN DESCRIPTION	
1	VSS
2	VSS
3	NC
4	VDD
5	VDD
6	VDD
7	VDD
8	VDD
9	WPN
10	SCL
11	SDA
12	VSS
13	VSS
14	VSS
15	RxOIN3-
16	RxOIN3+
17	VSS
18	RxOCKIN-
19	RxOCKIN+
20	VSS
21	RxOIN2-
22	RxOIN2+
23	VSS
24	RxOIN1-
25	RxOIN1+
26	VSS
27	RxOIN0-
28	RxOIN0+
29	VSS
30	VSS
31	NC
32	FB1
33	FB2
34	FB3
35	FB4
36	NC
37	NC
38	NC
39	VLED
40	VLED
41	VLED
42	VLED
43	VLED
44	NC
45	VSS

Specification:

- 1). Display mode: AHVA, Normally Black
- 2). Operating temp.: $-20^{\circ}\text{C} \sim +70^{\circ}\text{C}$
- 3). Storage temp.: $-30^{\circ}\text{C} \sim +80^{\circ}\text{C}$
- 4). Rohs complacant
- 5). "*" means important dimension

CUSTOMER APVL		DATE
DRAWN	SCALE	TITLE
DFTG CHK	UNIT	MI1010MT-1
ENGR CHK	mm	MODEL
APPROVAL		DWG NO
MULTI-INNO TECHNOLOGY CO.,LTD.		PAGE
		1/1