



PIN DESCRIPTION

Pin	Symbol
1	VCC
2	VCC
3	VSS
4	VSS
5	RIN0-
6	RIN0+
7	VSS
8	RIN1-
9	RIN1+
10	VSS
11	RIN2-
12	RIN2+
13	VSS
14	RCLK-
15	RCLK+
16	VSS
17	VDD_5V
18	VDD_5V
19	ADJ
20	VSS



Scale 50:1



39-LED WHITE 260MA/9.6V

NOTES:

1. DISPLAY TYPE: TFT, TRANSMISSIVE, NORMALLY WHITE.
2. OPERATING VOLTAGE: VDD=3.3V.
3. VIEWING DIRECTION: 12 O'CLOCK.
4. IC DRIVER: TBD.
5. OPERATING TEMP: -20°C ~ 70°C.
6. STORAGE TEMP: -30°C ~ 80°C.
7. SURFACE LUMINANCE: 450cd/m².
8. LED BACKLIGHT: 39-CHIP WHITE LED, If=260mA, Vf=9.6V.
9. GENERAL TOLERANCE: ±0.2.
10. RoHS COMPLIANT.

MULTI-INNO TECHNOLOGY CO.,LTD.			
DRAWN BY:	CAROL 2015.03.16	SCALE : 1/1	MODULE P/N:
CHECKED BY:		UNIT: mm	MI1010ZT-1
APPROVED BY:			DESCRIPTION:
VERSION NO:	01		GRAPHIC MODULE

01	FIRST ISSUE	2015.03.16
VER.	REVISED DESCRIPTION	DATE