


PIN ASSIGNMENT

NO.	NAME
1	DE
2	GND
3	GND
4	GND
5	NC
6	R0
7	R1
8	R2
9	R3
10	R4
11	R5
12	G0
13	G1
14	G2
15	G3
16	G4
17	G5
18	B0
19	B1
20	B2
21	B3
22	B4
23	B5
24	SCL
25	SDA
26	/CS
27	DOTCLK
28	/RESET
29	HSYNC
30	VSYNC
31	VCC
32	VCC
33	GND
34	LED A
35	LED K
36	GND
37	NC
38	NC
39	NC
40	NC

NOTES:

1. DISPLAY TYPE: A1FF, TRANSFLECTIVE, NORMALLY BLACK.
2. OPERATING VOLTAGE: VCC=2.8V, IOVCC=1.8V
3. VIEWING DIRECTION: WIDE VIEWING.
4. IC DRIVER: HX8363A
5. OPERATING TEMP: -20°C ~ 70°C.
6. STORAGE TEMP: -30°C ~ 80°C.
7. LED BACKLIGHT: 6-CHIP WHITE LED.
8. GENERAL TOLERANCE: ±0.2.
9. (...) IS REFERENCE DIMENSION.
10. * CRITICAL DIMENSION.
10. CONNECT: 54104-4090.
11. RoHS COMPLIANT.



BACKLIGHT LED CIRCUIT

CUSTOMER APVL		DATE
DRAWN	SCALE	TITLE
DFTG CHK	UNIT	MI0350ALT-1
ENGR CHK	mm	MODEL
APPROVAL		
MULTI-INNO TECHNOLOGY CO.,LTD.		DWG NO
		PAGE 1/1