



NOTE:

1. Tolerance is ± 0.3 unless otherwise noted.
2. CN1 connector: Starconn 076B20-0048RA-G4 or equivalent.
3. CN3 connector: LM123S-004-H-TF1-3 or equivalent.
4. For RoHS.
5. Center brightness: 1000 cd/m^2 (Typ.)
6. Uniformity: 70% (Min.)
7. * is important dimension.
8. The bending radius of FPC should be larger than 1.0mm.

CN1		
1	RX3+	11 GND
2	RX3-	12 RX1+
3	NC	13 RX1-
4	FRC	14 GND
5	GND	15 RX0+
6	RXC+	16 RX0-
7	RXC-	17 LR
8	GND	18 UD
9	RX2+	19 VCC
10	RX2-	20 VCC

CN3	
1	VLED
2	ADJ
3	EN
4	GND



MULTI-INNO TECHNOLOGY CO.,LTD.

DRAWN BY:	CAROL	2014.09.13	SCALE : 1/1	MODULE P/N:
CHECKED BY:			UNIT: mm	MI0700AQT-1
APPROVED BY:			DESCRIPTION:	TFT MODULE
VERSION NO:	01			

01	FIRST ISSUE	2014.09.13
VER.	REVISED DESCRIPTION	DATE